



- Elements:
- 1 L Fix Bracket 120x60x60x3mm. ALU 6063 T5.
 - 2 L Stop Bracket 60x60x60x3mm. ALU 6063 T5.
 - 3 Cerámica Piece 600x300mm.
 - 4 Vertical FTS Y Profile . 85x65x1.8mm. Alu 6063 T5.
 - 5 Vertical FTS Y Corner Profile . 50x65x1.8mm. Alu 6063 T5.
 - 6 Start/End FTS Supporting Clip. Stainless Steel.
 - 7 Intermediate FTS Supporting Clip. Stainless Steel.
 - 8 Fixed Point. DIN 7504K 5.5x22 SSA2.
 - 9 Sliding Point. DIN 7504K 5.5x22 SSA2.
 - 10 Expansive Stainless Steel Anchor M8x75.
 - 11 Quematic Anchor M10x80.
 - 12 Pin. Din 6060 5x20
 - 13 EPDM Profile.

Notes:

- Facade Standard* Distance:
- L-60: X=100-140mm
- L-100: X=140-180mm
- L-140: X=180-220mm
- * Smaller or higher distances under request.

Project: FTS 502B-Y GA 16mm	
Plan n: FTS_502B-Y_GA16	
Date: 03/12/2015	
Rev: 03	
Scale: 1:6	
Format: A2	Measures in mm
Ctra Escatrón, 9 44600 Alcañiz, Teruel (SPAIN) +34 978 830 511 · www.faveker.com	